

# Submittal Data

# Well-Rite Series

## Water System Tanks

Job Name: \_\_\_\_\_ Schedule #: \_\_\_\_\_

Location: \_\_\_\_\_ Model #: \_\_\_\_\_

Engineer: \_\_\_\_\_ Representative: \_\_\_\_\_

Contractor: \_\_\_\_\_

### Materials of Construction

Shell: Drawn steel w/ epoxy finish

Diaphragm: Butyl rubber w/ copolymer polypropylene lower water chamber

Connection: Stainless steel

### Ratings

Max. Working Pressure: 125 PSI

Max. Working Temp: 140 F

Pre-Charge (adjustable): 38 PSI

### Description

Well-Rite (WR) series tanks are diaphragm type pre-charged hydro-pneumatic tanks designed for residential and commercial water wells, pressure booster, irrigation and reverse osmosis systems.



### Tank Specifications

Model	Diameter (inches)	Height (inches)	System Connection (inches)	Volume (gallons)	Drawdown (gallons)			Weight (lbs)
					20/40	30/50	40/60	
WR 45	16	22	1	14	5.6	4.8	4.1	28
WR 60	16	29	1	20	8.1	6.8	5.9	36
WR 80	16	34.5	1	26	10.5	8.9	7.7	41
WR 100	21	27.75	1 ¼	32	12.9	10.9	9.4	54
WR 120	16	42.75	1	33.4	13.3	11.3	9.7	49
WR 140	21	36.25	1 ¼	44	17.7	15.0	13.0	67
WR 200	21	48	1 ¼	62	25.0	21.1	18.3	82
WR 240	21	62	1 ¼	81	32.6	27.6	23.9	99
WR 260	26	44.5	1 ¼	85	34.3	29.0	25.1	121
WR 360	26	59.75	1 ¼	119	48.0	40.6	35.1	153

